

TUBOLED GLASS VB



- * Base: G13.
- * Operating voltage 100-240V.
- * Milky white diffuser.
- * 330° opening beam: wide lighting distribution curve.
- * Color rendering > 80.
- * Operating voltage 220-240V.
- * Working position: universal.
- * Replacing from 18W to 58W T8 tubes: high energy saving.
- * Immediate switch on, no flickering or buzzes.
- * Great flow maintenance.
- * USAGE INFORMATION
- * Do not use with dimmers.
- * In case fluorescent tubes must be replaced, follow the simple assembly instructions on the mounting instruction sheet.
- * Do not use in installations in series.

Item Characteristics

Code	L58840VB
Lamp Voltage	220-240 V
Nominal Power	24 W
Base	G13
Lamp Current	0,21 A
Nominal Flux	2500 LUMEN
Light Tonality	Natural white
Colour temperature	4000 K
Opening beam	330°
Diameter	29 mm
Length	1500 mm

Performance

Photometry	F185
Irc/Ra	>80
Lifetime	25000 h
Energy Class	A+
kWh/1000h	24
Equivalence with incandescent lamp	153 W

Tech Info

Dimmable	NO
Operating Position	360°
Open fittings	YES
Number of ON-OFF cycles	100000

All parts of this document are Duralamp ownership. All rights reserved. This document and the included information are provided without any responsibility deriving from mistakes or omissions. No part of this document can be cut, reproduced or used without written authorization. Duralamp maintains the right to change the included data without notice due to improvements of the products.

Power Factor	0,5
Warm-up time up to 60 % of the full light output	Instant Full Light
Lamp start time	<0,2s
Mercury (mg)	0
LLMMF - Lamp lumen maintenance factor	70
T (°C) Working environment Temp.	-25°C / +35°C
Fulfilled Directives and norms	2011/65/UE * RoHS 2012/19/UE * RAEE 2014/30/UE * Compatibilità Elettromagnetica 2014/35/UE * Bassa Tensione EN 61547 * anno 2010 EN 55015 * anno 2014 EN 61000-3-2 * anno 2007 (+A1/+A2:2011) EN 61000-3-3 * anno 2014 EN 62471 * anno 2010 IEC/TR 62471-2:2009 (CEI 34-141:2012 EN 62031 * anno 2009 (+A1:2013) EN 60598-1 * anno 2009 EN 60598-2-1 * anno 1997 EN 61347-1 * anno 2009 (+A1:2011, +A2:2013) EN 61347-2-13 * anno 2007 EN 62031 * anno 2009 (+A1:2013) EN 62493 * anno 2010 EN 62776 Gruppo di rischio 0 2010/30/EU * Energy Consumption 874/2012 * Regulation for Energy Labelling 2009/125/CE * Progettazione Eco Compatibile 1194/2012 * Progettazione Eco Compatibile

Spectrocolorimetry and Photometry

Eulumdat file for lighting calculations available on the website

Shipping info

Single pack dimensions L x H x D (mm)	1620 x 30 x 30
Item barcode	8011905845551
Pack	10 pz
Inner pack dimensions L x H x D (mm)	1620 x 180 x 80
Master barcode	8011905845568